

# Packaging Feeder Series

## Innovative friction feeders featuring dynamic rotation technology

The Packaging Feeder Series (PC or PS models) are available in widths ranging from 6" to 18". These feeders come standard with the Patented Dynamic Rotation Technology, Batch Count (PC only), Time Delay, Auto Restart, Single Shot, Anti-Glaze Belt Formula, 1/4" thick powder coated side frames, Business Card Guides and Variable Speed Control. Series available in either the single shot on demand (PS) or batch counting option (PC).

Wrapping, inserting, traying and fulfillment applications can be automated by the use of an on-demand feeder. Each feeder can be integrated into your existing packaging line to deliver product into a predetermined position on the host machine.

Miss and double detect helps with integrity by either stopping the host machine or sending a signal to activate a divert station.

With the batch counting option, the user-friendly interface lets you program your specific job requirements.

The batch counter LCD screen is easy to read and set up. The batch mode with the auto restart option can be activated to count out a pre-set count, pause for a pre-set duration of time and then automatically allow you to maximize the output from the feeder to the application at speeds of more than 60,000 per hour.

Servo motor upgrade available. This upgrade allows the feeder to follow the host machine speed for precision placement.



SE 1200 PC

### Feedable Material

- > Instruction Booklets
- > Phone Cards
- > 20 lbs Bond to 200 lbs Index
- > Chipboard
- > Corrugated Cardboard
- > Plastics
- > Booklets
- > Pamphlets
- > Envelopes
- > Magnets
- > Perfect Bound
- > Saddle Stitch Books
- > Sleeved CDs
- > Cases

# Packaging Feeder Series

## Available Models

	SE 600 PC/PS	SE 900 PC/PS	SE 1200 PC/PS	SE 1800 PC
Max. Product Size	6.5" w x 14" l	9" w x 14" l	12" w x 14" l	18" w x 14" l
Min. Product Size	2.5" w x 2" l	2.5" w x 2" l	3" w x 2" l	3" w x 2" l
Max. Thickness Size	.5"	.5"	.5"	.5"
Min. Thickness Size	.002"	.002"	.002"	.002"
Feeder Capacity	20" vertical	20" vertical	20" vertical	20" vertical
Speed	20 to 525 ft./min.	20 to 525 ft./min.	20 to 525 ft./min.	20 to 525 ft./min.
Time Delay	10 ms. – 5 sec.	10 ms. – 5 sec.	10 ms. – 5 sec.	10 ms. – 5 sec.
Sensor Trigger	Triangulated Beam	Triangulated Beam	Triangulated Beam	Triangulated Beam
Electrical	120/240 VAC	120/240 VAC	120/240 VAC	120/240 VAC
Drive Motor	Variable DC	Variable DC	Variable DC	Variable DC

## Options Available

- > Fault Output
- > Encoder
- > Small Product Setup
- > Double Detection
- > Trigger Interface
- > Gear Down
- > Speed Following
- > Credit Card Guides
- > Bulk Autoloader
- > Low Product Sensor
- > Thicker Feed Upgrades
- > Catch Tray
- > Stand
- > Extended Hoppers
- > ECO Models
- > Servo Drive Upgrades

**ALL COME WITH 2 YEAR LIMITED/90 DAY ELECTRICAL WARRANTY**

**For more information call 1-800-467-3783  
or contact your local Pitney Bowes office.**

Pitney Bowes has the software, services and hardware for end-to-end mailstream solutions that integrate and optimize the flow of mail, documents and packages across a range of business operations.

Pitney Bowes, the corporate design and Engineering the flow of communication are registered trademarks. All other products referenced in this material may be trademarks or registered trademarks of their respective companies.



**Pitney Bowes Sure-Feed Engineering**  
12050 49th Street N.  
Clearwater, FL 33762  
Tel: 800.467.3783  
727.571.3330  
Web: [www.surefeed.com](http://www.surefeed.com)

**Pitney Bowes Inc.**  
37 Executive Drive  
Danbury, CT 06810-4148  
Tel: 877.536.2736  
203.792.1600  
Web: [www.pbdmt.com](http://www.pbdmt.com)